


PowerCache® – S (72 kVA / 72 kWh) Datasheet

<p style="text-align: center;">PowerCache® – S: Grid-in-a-Box</p> <p>PowerCache is a utility-grade grid in a box. It enables operators of ultra-fast EV charging, commercial or industrial sites, microgrids and communities to provide an unconstrained power user experience on a constrained network. This versatile power system combines a robust, ultra-rapid-response power converter/ controller and a high-performance battery with intelligent microgrid control. PowerCache is expandable and integrates with other systems on-site. It can participate in ancillary services markets.</p>	 <p style="font-size: small;">Pole-mounted version for illustration only – Details are for a ground-mounted system</p>
--	---

System Performance	
Nominal frequency and voltage	47Hz ... 53Hz, 415V or 400V +10%/-6%
Grid connection	3-phase+N, YNd transformer-coupled
Active and reactive power rating	$S_{Nom} = 72 \text{ kVA}$ - 4-quadrant P&Q, symmetrical apparent power available
Inverter maximum continuous load	3-phase: $S_{Nom} = 72 \text{ kVA}$ Single phase: $S_{Nom}/\sqrt{3}$ (other phases not loaded)
Permissible phase load imbalance	Unlimited within the rating per phase +/-
Inverter base electrical function	<ul style="list-style-type: none"> • Current source (on-grid) • Virtual synchronous machine (on- & off-grid, various load-sharing modes)
Harmonics	Compliant with AS4777.2
Reaction time ext signal / step load	<50 ms / <50 ms
Primary frequency control step response – rise time / settling time	User definable via generator time constant and frequency PID control, typically: 150 ms / 1500 ms
System overload capability	400% instantaneous, 166% for 2 s, 125% for 1 minute in 10 minutes
AC protection	Over/under current/voltage/frequency, two locations (inter-tie), various timings, RoCoF, VVS, negative sequence voltage, sync-checks, active and passive 3-phase and single-phase anti-islanding to AS4777, insulation monitoring
Application-level protections	Over/under SoC, sustained overvoltage, protection consistency checks, application alarms, safe states after system transition failures, etc, via the PaDECS® control system
DC protection	Insulation monitoring, overcurrent/voltage, Battery OEM protections
System AC-AC round trip efficiency	>89% for a typical application scenario.


Battery Performance	
Rated total DC energy	> 72 kWh
Battery chemistry	NMC cathode, LiNi _x Mn _y Co _z O ₂ , pouch cell structure
Indicative battery cycle life / full cycle equivalents (FCE)	4,000 FCE at 90% DoD to 70% capacity retention; or 5,000 FCE at 80% DoD to 70% capacity retention
Battery calendar life	>13 years
Battery Protection	Cell- and system-level supervision, control and protection of current, voltage, power, SoC, SoH, temperature, imbalances in these quantities, insulation and component failures

Interface	
Web-API	Web-API via VPN
SCADA	Modbus TCP or discrete hardwired alarms and E-Stop
System HMI	GUI web application via VPN
Local data Historian Client	Logging all system features, parameters, modes and actuals, access via VPN
Cloud-Client GUI and API	Cloud-Client GUI and API via the PaDECS® portfolio & market cloud aggregator service (SaaS)
Direct component Web-HMIs	Engineering access to protection relay, inverter, battery and auxiliaries

Mechanical	
Fire mitigation	Smoke & heat detection, Novec® gaseous fire suppression system with detector tube
Cabinet cooling	Forced air cooling, air inlet: door louvres, outlet: roof frame – noise optimised
Cabinet structure	Single-walled, lined with heat & noise protective foam
Dimensions	Height x Width x Depth = 1,900 mm x 1,100 mm x 1,100 mm
Weight	1,600 kg

Environmental	
Humidity	5% to 100% outside 5% to 95%, non-condensing inside cabinet
Altitude	Up to 1,000 m without derating
Inverter System Module	
Operating ambient temperature	0 – 40° C without derating, 0 – 55° C max
Noise (max. @ 1 m distance)	<55 dBA
IP Rating	IP54 outdoor cabinet

Compliance	
AS/NZS 4777.2:2020	The inverter/filter assembly is compliant, but not yet certified for the size (105A). Certificate No. SAA192864 for a larger assembly is used for negotiated grid connection approval.
AS 5139	Safety of battery systems for use with power conversion equipment
IEC 61000 (Part 3)	EMC emission limits
EN 61800	EMC requirements for adjustable speed electrical power drive systems
AS 3000	Electrical wiring rules
AS 3800	Selection of cables for alternating voltages up to 0.6 / 1 kV
EN 61558-2-1	Safety of power transformers



Contact
Power Technology Engineered Solutions Pty Ltd Unit 18/25 Cook Road Mitcham 3132, Australia power-tec.com.au